

# Pivoting Landing Ladder

*Safety Every Step of the Way*

Providing safe trailer access can result in decreased Workers Compensation Claims and absenteeism due to injury, and increased productivity & profitability.



Designed in collaboration with our customers, the **Bustin Pivoting Landing Ladder** provides a portable solution to reefer trailer side door unloading. One unit can service multiple trailer doors. The ample 24" x 24" landing folds down so that the entire unit can be stowed away flat. The steps & landing feature our Bustin Serrated Safety Grating for optimal slip-resistance. The aluminum extrusion nosing on the steps provides a visible, slip-resistant leading edge for an extra measure of safety & strength. Designed, tested & rated for 500 lbs, the **Pivoting Landing Ladder** delivers Bustin reliability & quality!



**Be Specific...  
Specify Bustin  
for Safety!**

## Features:

- All aluminum design—no rust!
- Unit folds flat to stow compactly in our Galvanized Enclosure.
- Pivoting 24 x 24 grating landing
- 6 3/8" wide safety grating treads & nosing.
- Grating provides non-slip, self-cleaning surface for an added measure of safety.
- 58° angled ladder for a more comfortable "stair-like" climb.
- 3" heavy-duty channel ladder rails
- **Two mounting styles available:**
  - Stainless steel Swivel Hooks fit into holes in floor.
  - Mounting Brackets can be bolted to outside of trailer

Each Galvanized Storage Box is shipped with versatile mounting straps for bolted or welded installation to truck frame. (Straps are shipped loose, not shown in photo.)



Pivoting Landing Ladder shown folded flat in stowed position

Model Number	Top of Landing To Ground	Mounting Method
679-APC-010	58"	Swivel Hooks
679-APC-011	58"	Mounting Brackets
679-APC-012	52"	Mounting Brackets
679-SPC-013 Galvanized Box	30 1/2 W x 85 L X 12 1/8 D	Bolt or weld to truck frame



ISO 9001 REGISTERED COMPANY

**BUSTIN INDUSTRIAL PRODUCTS, Inc.**

[www.bustin-usa.com](http://www.bustin-usa.com)

Tollfree: (800) 933-5166  
Phone: (570) 424-6500  
FAX: (570) 424-6453